

Analysis of Algorithms

CS 477/677

Instructor: Monica Nicolescu

Lecture 16

Dynamic Programming


- An algorithm design technique used for **optimization problems**
 - Find a solution with the **optimal value** (minimum or maximum)
 - A set of **choices** must be made to get an optimal solution
 - There may be multiple solutions that return the optimal value: we want to find one of them

Dynamic Programming Algorithm

1. Characterize the structure of an optimal solution
 - **Top down:** how can an optimal value for a problem be obtained from combinations of optimal solutions to similar, smaller problems of the same type
2. Recursively define the value of an optimal solution
 - **Top down:** write a recursive formula based on the step above
3. Compute the value of an optimal solution
 - **Bottom up:** compute *“smaller subproblems”* first, store **values** and **choices** made at each step
4. Construct an optimal solution
 - **Top down:** start with last choice made and backtrack, finding all choices made

Assembly Line Scheduling

- Problem:
What stations should be chosen from line 1 and what from line 2 in order to **minimize the total time through the factory for one car?**



Dynamic Programming Algorithm

1. Characterize the structure of an optimal solution
 - Fastest time through a station depends on the fastest time on previous stations
2. Recursively define the value of an optimal solution
 - $f_1[j] = \min(f_1[j-1] + a_{1,j}, f_2[j-1] + t_{2,j-1} + a_{1,j})$
3. Compute the value of an optimal solution in a bottom-up fashion
 - Fill in the fastest time table in increasing order of j (station #)
4. Construct an optimal solution from computed information
 - Use an additional table to help reconstruct the optimal solution

Matrix-Chain Multiplication

Problem: given a sequence $\langle A_1, A_2, \dots, A_n \rangle$ of matrices, compute the product:

$$A_1 \bullet A_2 \bullet \dots \bullet A_n$$

- Matrix compatibility:

$$C = A \bullet B$$

$$\text{col}_A = \text{row}_B$$

$$\text{row}_C = \text{row}_A$$

$$\text{col}_C = \text{col}_B$$

$$A_1 \bullet A_2 \bullet A_i \bullet A_{i+1} \bullet \dots \bullet A_n$$

$$\text{col}_i = \text{row}_{i+1}$$

Matrix-Chain Multiplication

- In what order should we multiply the matrices?

$$A_1 \cdot A_2 \cdot \dots \cdot A_n$$

- Matrix multiplication is associative:


- **E.g.:** $A_1 \cdot A_2 \cdot A_3 = ((A_1 \cdot A_2) \cdot A_3)$
 $= (A_1 \cdot (A_2 \cdot A_3))$

- Which one of these orderings should we choose?
 - The order in which we multiply the matrices has a significant impact on the overall cost of executing the entire chain of multiplications

MATRIX-MULTIPLY(A, B)

```
if columns[A]  $\neq$  rows[B]  
  then error "incompatible dimensions"  
else for  $i \leftarrow 1$  to rows[A]  
  do for  $j \leftarrow 1$  to columns[B]  
    do  $C[i, j] = 0$   
    for  $k \leftarrow 1$  to columns[A]  
      do  $C[i, j] \leftarrow C[i, j] + A[i, k] B[k, j]$ 
```

rows[A] • cols[A] • cols[B]
multiplications



Example

$$A_1 \cdot A_2 \cdot A_3$$

- A_1 : 10×100
- A_2 : 100×5
- A_3 : 5×50

1. $((A_1 \cdot A_2) \cdot A_3)$: $A_1 \cdot A_2$ takes $10 \times 100 \times 5 = 5,000$

(its size is 10×5)

$((A_1 \cdot A_2) \cdot A_3)$ takes $10 \times 5 \times 50 = 2,500$

Total: 7,500 scalar multiplications

2. $(A_1 \cdot (A_2 \cdot A_3))$: $A_2 \cdot A_3$ takes $100 \times 5 \times 50 = 25,000$

(its size is 100×50)

$(A_1 \cdot (A_2 \cdot A_3))$ takes $10 \times 100 \times 50 =$

50,000

Total: 75,000 scalar multiplications

Matrix-Chain Multiplication

- Given a chain of matrices $\langle A_1, A_2, \dots, A_n \rangle$, where for $i = 1, 2, \dots, n$ matrix A_i has dimensions $p_{i-1} \times p_i$, fully parenthesize the product $A_1 \cdot A_2 \cdots A_n$ in a way that minimizes the number of scalar multiplications.

$$\begin{array}{ccccccc} A_1 & \cdot & A_2 & \cdots & A_i & \cdot & A_{i+1} & \cdots & A_n \\ p_0 \times p_1 & p_1 \times p_2 & p_{i-1} \times p_i & p_i \times p_{i+1} & p_{n-1} \times p_n \end{array}$$

1. The Structure of an Optimal Parenthesization

- Notation:

$$A_{i\dots j} = A_i A_{i+1} \dots A_j, i \leq j$$

- For $i < j$:

$$\begin{aligned} A_{i\dots j} &= A_i A_{i+1} \dots A_j \\ &= A_i A_{i+1} \dots A_k A_{k+1} \dots A_j \\ &= A_{i\dots k} A_{k+1\dots j} \end{aligned}$$

- Suppose that an optimal parenthesization of $A_{i\dots j}$ splits the product between A_k and A_{k+1} , where $i \leq k < j$

Optimal Substructure

$$A_{i\dots j} = A_{i\dots k} A_{k+1\dots j}$$

- The parenthesization of the “prefix” $A_{i\dots k}$ must be an optimal parenthesization
- If there were a less costly way to parenthesize $A_{i\dots k}$, we could substitute that one in the parenthesization of $A_{i\dots j}$ and produce a parenthesization with a lower cost than the optimum \Rightarrow contradiction!
- An optimal solution to an instance of the matrix-chain multiplication contains within it optimal solutions to subproblems

2. A Recursive Solution

- Subproblem:

determine the minimum cost of parenthesizing

$$A_{i\dots j} = A_i A_{i+1} \cdots A_j \quad \text{for } 1 \leq i \leq j \leq n$$

- Let $m[i, j]$ = the **minimum** number of multiplications needed to compute $A_{i\dots j}$
 - Full problem ($A_{1\dots n}$): $m[1, n]$
 - $i = j$: $A_{i\dots i} = A_i \Rightarrow m[i, i] = 0$, for $i = 1, 2, \dots, n$

2. A Recursive Solution

Consider the subproblem of parenthesizing

$$A_{i\dots j} = A_i A_{i+1} \dots A_j \quad \text{for } 1 \leq i \leq j \leq n$$

$$= A_{i\dots k} A_{k+1\dots j} \quad \text{for } i \leq k < j$$

- Assume that the optimal parenthesization splits the product $A_i A_{i+1} \dots A_j$ at k ($i \leq k < j$)

$$m[i, j] = \underbrace{m[i, k]} + \underbrace{m[k+1, j]} + \underbrace{p_{i-1}p_kp_j}$$

min # of multiplications
to compute $A_{i\dots k}$

min # of multiplications
to compute $A_{k+1\dots j}$

of multiplications
to compute $A_{i\dots k} A_{k\dots j}$

2. A Recursive Solution


$$m[i, j] = m[i, k] + m[k+1, j] + p_{i-1}p_kp_j$$


- We do not know the value of k
 - There are $j - i$ possible values for k : $k = i, i+1, \dots, j-1$
- Minimizing the cost of parenthesizing the product $A_i A_{i+1} \dots A_j$ becomes:

$$m[i, j] = \begin{cases} 0 & \text{if } i = j \\ \min_{i \leq k < j} \{m[i, k] + m[k+1, j] + p_{i-1}p_kp_j\} & \text{if } i < j \end{cases}$$

3. Computing the Optimal Costs

$$m[i, j] = \begin{cases} 0 & \text{if } i = j \\ \min_{i \leq k < j} \{m[i, k] + m[k+1, j] + p_{i-1}p_kp_j\} & \text{if } i < j \end{cases}$$

- How many subproblems do we have?
 - Parenthesize $A_{i...j}$ for $1 \leq i \leq j \leq n \Rightarrow \Theta(n^2)$
 - One subproblem for each choice of i and j
- 
- | | | | |
|---|---|---|---|
| | 1 | 2 | 3 |
| 1 | | | |
| 2 | | | |
| 3 | | | |



3. Computing the Optimal Costs

$$m[i, j] = \begin{cases} 0 & \text{if } i = j \\ \min_{i \leq k < j} \{m[i, k] + m[k+1, j] + p_{i-1} p_k p_j\} & \text{if } i < j \end{cases}$$

- How do we fill in table $m[1..n, 1..n]$?
 - Determine which entries of the table are used in computing $m[i, j]$

$$A_{i\dots j} = A_{i\dots k} A_{k+1\dots j}$$

- Fill in m such that it corresponds to solving problems of increasing length


3. Computing the Optimal Costs

$$m[i, j] = \begin{cases} 0 & \text{if } i = j \\ \min_{i \leq k < j} \{m[i, k] + m[k+1, j] + p_{i-1}p_kp_j\} & \text{if } i < j \end{cases}$$

- Length = 1: $i = j, i = 1, 2, \dots, n$
- Length = 2: $j = i + 1, i = 1, 2, \dots, n-1$


$m[1, n]$ gives the optimal solution to the problem

Compute elements on each diagonal, starting with the longest diagonal.
In a similar matrix s we keep the optimal values of k .



Example: $\min \{m[i, k] + m[k+1, j] + p_{i-1}p_kp_j\}$

$$m[2, 5] = \min \begin{cases} m[2, 2] + m[3, 5] + p_1 p_2 p_5 & k = 2 \\ m[2, 3] + m[4, 5] + p_1 p_3 p_5 & k = 3 \\ m[2, 4] + m[5, 5] + p_1 p_4 p_5 & k = 4 \end{cases}$$



- Values $m[i, j]$ depend only on values that have been previously computed

Example $\min \{m[i, k] + m[k+1, j] + p_{i-1}p_kp_j\}$

Compute $A_1 \cdot A_2 \cdot A_3$

- $A_1: 10 \times 100$ ($p_0 \times p_1$)
- $A_2: 100 \times 5$ ($p_1 \times p_2$)
- $A_3: 5 \times 50$ ($p_2 \times p_3$)

$m[i, i] = 0$ for $i = 1, 2, 3$

$$m[1, 2] = m[1, 1] + m[2, 2] + p_0p_1p_2 \quad (A_1A_2)$$

$$= 0 + 0 + 10 * 100 * 5 = 5,000$$

$$m[2, 3] = m[2, 2] + m[3, 3] + p_1p_2p_3 \quad (A_2A_3)$$

$$= 0 + 0 + 100 * 5 * 50 = 25,000$$

$$m[1, 3] = \min \left\{ \begin{array}{l} m[1, 1] + m[2, 3] + p_0p_1p_3 = 75,000 \quad (A_1(A_2A_3)) \\ m[1, 2] + m[3, 3] + p_0p_2p_3 = 7,500 \quad ((A_1A_2)A_3) \end{array} \right.$$

	1	2	3
3	² 7500	² 25000	0
2	¹ 5000	0	
1	0		

4. Construct the Optimal Solution

- **Top-down** approach
- Store the optimal choice made at each subproblem
- $s[i, j] = \text{a value of } k \text{ such that an optimal parenthesization of } A_{i..j} \text{ splits the product between } A_k \text{ and } A_{k+1}$

	1	2	3			n
n						
			k			
3						
2						
1						

j

i

4. Construct the Optimal Solution

- $s[1, n]$ is associated with the entire product $A_{1..n}$

- The final matrix multiplication will be split at $k = s[1, n]$

$$A_{1..n} = A_{1..k} \cdot A_{k+1..n}$$

$$A_{1..n} = A_{1..s[1, n]} \cdot A_{s[1, n]+1..n}$$

- For each subproduct recursively find the corresponding value of k that results in an optimal parenthesization

	1	2	3		n	
n						
3						
2						
1						

4. Construct the Optimal Solution

- $s[i, j]$ = value of k such that the optimal parenthesization of $A_i A_{i+1} \dots A_j$ splits the product between A_k and A_{k+1}

	1	2	3	4	5	6
6	3	3	3	5	5	-
5	3	3	3	4	-	
4	3	3	3	-		
3	1	2	-			
2	1	-				
1	-					

i

j

- $s[1, 6] = 3 \Rightarrow A_{1..6} = A_{1..3} A_{4..6}$
- $s[1, 3] = 1 \Rightarrow A_{1..3} = A_{1..1} A_{2..3}$
- $s[4, 6] = 5 \Rightarrow A_{4..6} = A_{4..5} A_{6..6}$

4. Construct the Optimal Solution

PRINT-OPT-PARENS(s, i, j)

if $i = j$

then print " A_i "

else

 print "("

 PRINT-OPT-PARENS($s, i, s[i, j]$)

 PRINT-OPT-PARENS($s, s[i, j] + 1, j$)

 print ")"

	1	2	3	4	5	6
6	3	3	3	5	5	-
5	3	3	3	4	-	
4	3	3	3	-		
3	1	2	-			
2	1	-				
1	-					

j

i

Example: $A_1 \bullet \bullet \bullet A_6 ((A_1 (A_2 A_3)) ((A_4 A_5) A_6))$

PRINT-OPT-PARENS(s, i, j)

if i = j

then print "A"_i

else print "("

PRINT-OPT-PARENS(s, i, s[i, j])

PRINT-OPT-PARENS(s, s[i, j] + 1, j)

print ")"

P-O-P(s, 1, 6)

i = 1, j = 6 "("

s[1, 6] = 3

P-O-P (s, 1, 3) s[1, 3] = 1

i = 1, j = 3 "(" P-O-P(s, 1, 1) ⇒ "A"₁

P-O-P(s, 2, 3) s[2, 3] = 2

i = 2, j = 3 "(" P-O-P (s, 2, 2) ⇒ "A"₂

P-O-P (s, 3, 3) ⇒ "A"₃

)"

)" ...


s[1..6, 1..6]

	1	2	3	4	5	6
6	3	3	3	5	5	-
5	3	3	3	4	-	
4	3	3	3	-		
3	1	2	-			
2	1	-				
1	-					

j

i

Readings



- For this lecture
 - Sections 6.3, 6,5
 - Chapter 13
- Coming next
 - Chapter 17